

Statistical Analysis of a Large Sample Size Pyroshock Test Data Set

William O. Hughes and Anne M. McNelis
Lewis Research Center, Cleveland, Ohio

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:


- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized data bases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at **<http://www.sti.nasa.gov>**
- E-mail your question via the Internet to **help@sti.nasa.gov**
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
NASA Access Help Desk
NASA Center for AeroSpace Information
800 Elkridge Landing Road
Linthicum Heights, MD 21090-2934



Statistical Analysis of a Large Sample Size Pyroshock Test Data Set

William O. Hughes and Anne M. McNelis
Lewis Research Center, Cleveland, Ohio

Prepared for the
68th Shock and Vibration Symposium
sponsored by the Shock and Vibration Information Analysis Center
Hunt Valley, Maryland, November 3–7, 1997

National Aeronautics and
Space Administration

Lewis Research Center

Acknowledgments

The authors would like to acknowledge the contributions and support of the following personnel: Bryan Smith of the NASA Lewis Launch Vehicle Project Office and Rick Manella, Kelly Carney and Mark McNelis of the NASA Lewis Engineering and Technical Services Directorate.

Available from

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076
Price Code: A03

National Technical Information Service
5287 Port Royal Road
Springfield, VA 22100
Price Code: A03

STATISTICAL ANALYSIS OF A LARGE SAMPLE SIZE PYROSHOCK TEST DATA SET

William O. Hughes and Anne M. McNelis
NASA Lewis Research Center
Engineering and Technical Services Directorate
21000 Brookpark Road
Cleveland, Ohio 44135
(216) 433-2597/8880

The EOS spacecraft will launch on an Atlas IIAS launch vehicle on its mission to planet Earth in late 1998. The new design of the spacecraft's pyroshock separation system was characterized by a series of thirteen separation tests. The analysis methods used to evaluate this unusually large amount of shock data will be discussed in this paper, with particular emphasis on population distributions and finding statistically significant families of data, leading to an overall shock separation interface level.

INTRODUCTION

In the aerospace industry, the availability of a meaningful valid set of pyroshock test data is often difficult to obtain. Obtaining a large sample size of such data is very rare. Recently, such a large sample size pyroshock test data set was obtained for a newly designed spacecraft separation system which will be employed for an upcoming NASA mission. In late 1998, NASA will launch the EOS (Earth Observing System) spacecraft to low Earth orbit, on a Lockheed-Martin Atlas IIAS launch vehicle. Due to EOS's truss structure and hardpoint spacecraft interface, the pyroshock spacecraft separation system utilized for this mission is of a new design. This separation system was test verified through numerous test firings, by both the launch vehicle contractor and the spacecraft contractor. This has resulted in an unusually large amount of shock test data. The availability of such a test data set allows a statistical evaluation of shock data which is seldom employed. Emphasis will be given to the population distribution of each data set and the proper combination of different data sets. Additionally the binomial distribution will be used to better characterize the separation shock level for this particular separation system.

SPACECRAFT SEPARATION SYSTEM

As part of the Lockheed-Martin Astronautics (LMA) IELV (Intermediate Expendable Launch Vehicle) Program, a 77 inch, six point hardpoint payload separation system (PSS77) was developed to provide structural attachment of the EOS spacecraft to the launch vehicle's payload adapter (PLA) during launch and ascent, until the operation of the system releases the spacecraft. Since EOS is the first mission using the PSS77, extensive testing of the system was performed by both the launch vehicle contractor (LMA, at Denver) and the spacecraft contractor (LMMS, Lockheed-Martin Missiles & Space, at Valley Forge).

The PLA is an inverted conical skin-stringer-ring structure. The six shear plates which mount on the forward ring of the PLA (as seen in Fig. 1a) correspond to the six nodes or hardpoints of the spacecraft. As shown in Fig. 1b, each shear plate is attached to the PLA by a separation stud and nut. The spacecraft hardpoints are connected to the shear plates by a number of tension bolts. When the separation nut pressure cartridge fires, the separation stud is released and is caught by the stud catcher assembly. Separation occurs between the PLA and the separation plate (which is now attached to the spacecraft). The separation impulse is provided by springs at each of the six nodes.

TEST CONFIGURATIONS

The test firing of the PSS77 was tested in different hardware configurations at LMA and at LMMS due to different organizational purposes.

The testing at LMA was done to verify the mechanical operation of the PSS77, especially the stud catcher design and to acquire and characterize the pyroshock levels produced by the separation system at various separation stud preload values. A total of twelve (12) test firings were performed over three different test series at LMA, which occurred from January 1996 through February 1997. Two (2) test firings were performed at LMMS in June-July 1996. Since LMMS is the EOS spacecraft contractor, the primary purpose of their testing was to acquire and characterize the pyroshock levels propagating from the spacecraft interface up the spacecraft. Hence two different test configurations were tested.

The LMA test configuration is shown in Figure 2. Approximately one-third of the full spacecraft mass of 11,000 pounds was simulated using the spacecraft stiffness simulator (SCSS). A flight-like PLA, a Centaur Equipment Module (CEM) with avionics components and a stub adapter were utilized. At separation, a mass counterweight was used to achieve the correct flight separation velocity for the SCSS. The PLA, CEM and stub adapter remained attached to the base fixture. Data was obtained at the six shear plate locations, at three PLA locations and at various components of the CEM. LMA acquired their test data on analog tape recorders (Honeywell).

The LMMS test configuration is shown in Figure 3. A full scale spacecraft simulator (11,000 pounds) with mass models for spacecraft instruments was utilized. A short CEM simulator without avionics hardware was used. No stub adapter was present in this testing. An overhead crane suspended the EOS spacecraft and PLA/CEM simulator assembly. At separation, the PLA/CEM simulator dropped approximately 3 inches onto a foam shock absorber pad. Shock data was obtained at the identical six shear plate and three PLA locations (as the LMA testing) and at numerous spacecraft instruments locations. LMMS acquired their test data digitally (Zonic).

DESCRIPTION OF TEST SERIES

The first series of testing, denoted as LMA 1-5, consisted of five separation firings. This testing was performed at LMA's Denver (Waterton) test facility, as were all the other LMA test series. Testing occurred from January 1996 through April 1996. Various stud preloads were tested (ranging from a very low value of 10,900 pounds to a high value of 24,000 pounds). Both developmental and qualified stud catchers were employed in this series as the stud catcher performance was being evaluated. (A sixth test, LMA 6, was also performed in this series. The purpose of LMA 6 was to measure the effect of ordnance sequencing on the shock levels. Although firing the separation nuts at different times did not significantly affect the shock levels, the data from this test was not utilized in the statistical study of this work.)

The second series of testing is denoted as LMMS 1-2 and occurred at Valley Forge. Testing was performed in June-July 1996. The nominal stud preload of 20,700 pounds were utilized in both of the two test firings.

The third series of testing was denoted as LMA 7-9. These three test firings occurred in September-October 1996. For the CEM avionics boxes, higher fidelity avionics simulators were employed and some new lower fidelity mass simulators were utilized starting with LMA test 7. A low, nominal and high stud preload were tested. Additionally, a positive stud retraction method was added to the stud catcher design starting with LMA test 7.




Figure 1a. Separation System View of Payload Adapter and Shear Plates [4]




Figure 1b. Section View of Separation System [4]





Figure 2. (above) LMA Test Configuration for Test Series: LMA 1-5, LMA 7-9 and LMA 10-12 [4]

Figure 3. (right) LMMS Test Configuration for Test Series: LMMS 1-2 [5]



The fourth and last series of testing was LMA 10-12. These three test firings occurred in February 1997. Again a low, nominal and high stud preload were tested. The separation nuts for LMA 10-12 were taken from a different production lot than all the rest of the EOS test firings. Also, a different CEM was utilized for this testing, along with two more additional CEM simulators.

A summary of the four test series is provided in Table 1. Endevco's 7255A accelerometers were used to measure the shock at the shear plate locations (see Fig. 1b) for all four test series. All the data discussed in this paper is from the axial shear plate measurements, which was generally five to ten times larger in magnitude than the radial or tangential measurements at the shear plate locations.

TEST SERIES	CONFIGURATION & TEST SITE	TEST DATES	NUT PRELOAD VALUES	NUT PRODUCTION LOT
LMA 1-5	#1 Denver	Jan. 96 - April 96	very low to high	# 1
LMMS 1-2	#2 Valley Forge	June 96 - July 96	nominal	# 1
LMA 7-9	#1 Denver	Sept. 96 - Oct. 96	low, nominal, high	# 1
LMA 10-12	#1 Denver	Feb. 97	low, nominal, high	# 2

Table 1. Summary of Test Series

STATISTICAL ANALYSIS OF EACH TEST SERIES

Each of the four test series were first analyzed to determine its probability distribution. A large data population is generated for each test series by combining all one-sixth octave bands into a single data base by using the method described by Manning [1]. Each shock response level (at each frequency) was normalized to have zero mean and unit variance. For example, for the LMA 1-5 test series, a normalized database of size 780 was generated (5 tests x 6 measurements per test x 26 one-sixth octave bands (560 to 10,000 Hz) per shock response measurement).

The normalized database is analyzed to determine its probability distribution. The data from each test series was analyzed looking at both the measured data (normal distribution) and the log of the measured data (lognormal distribution). The analysis consisted of plotting probability distributions and histograms and calculating the median (first moment), skew (third moment) and kurtosis (fourth moment) of each normalized database. Duncan [2] is a useful resource in determining significantly appropriate skew and kurtosis values as a function of database size.

The conclusion was that the shock test data obtained in each of the four test series was lognormally distributed. This finding is consistent with past practices and with the guidelines of the NASA pyroshock standard [3]. The large amount of test data available in this testing enabled a statistical basis for the lognormal distribution instead of just assuming it to be true, as is often the case.

Fig. 4 - 7 show the shock response measurements for each of the four test series. In all cases, the measured data is fairly repeatable and shows a smaller test to test variability than is often seen for payload separation shock test data.




Figure 4. LMA 1-5
Shear Plate Data (30 Measurements)




Figure 5. LMMS 1-2
Shear Plate Data (12 Measurements)




Figure 6. LMA 7-9
Shear Plate Data (18 Measurements)




Figure 7. LMA 10-12
Shear Plate Data (18 Measurements)


STATISTICAL COMBINATION OF TEST SERIES

At this point there are four lognormal series of data. The next question to answer is “Can we statistically combine any or all of these data sets?” before calculating statistical levels. The criterion used for a successful combination was twofold. First, the combined data set must be in itself a lognormal distribution. Secondly, the combination was allowed only if the individual data series has means and standard deviations which were not statistically significantly different with a 95% confidence level. This last criteria was analyzed based on F-testing of the standard deviations and t-testing of the means.

Using these criterion, it was found that it was proper to combine LMA 1-5 and LMA 7-9. The means and standard deviations of these two test series were not statistically significantly different and their combined normalized database was lognormally distributed. Fig. 8 shows this combined data set, now denoted as LMA 1-9. The combined data set graphically appears to be one family.

Next, the combination of the new data set LMA 1-9 with LMMS 1-2 was analyzed. It was found to be an invalid combination for two reasons. First, the combined distribution was not lognormal. Secondly, the individual means were found to be significantly different as defined by the t-testing. Looking at Fig. 5 and 8, it appears that there are differences in the shock response between these two data sets (i.e. two high frequency peaks for LMA 1-9 and one high frequency peak for LMMS 1-2) to agree with the statistically conclusion to keep these two sets separate. It is thought that the differences in the two basic test configurations causes this result.

Finally, the combination of data sets LMA 1-9 and LMA 10-12 was analyzed. In this case the combined distribution was lognormal and the F-test of the standard deviations passed. However, the t-testing of the means were found to be significantly statistically different and thus this combination was not allowed. Looking at Fig. 7, one can see that the general spectral trend of LMA 10-12 is consistent with (the minimum and maximum of) LMA 1-9. However, the LMA 10-12 data is generally between the minimum and the mean of the LMA 1-9 data sets. Thus the statistical conclusions of different means is visualized. It is theorized that the lot to lot variation in the separation nut production lots contributed to this difference. (Note: the separation nuts that will be used for the EOS flight is from production lot #2, which appears to give lower shock levels based on the LMA 10-12 test data.)



**Figure 8. LMA 1-9
Shear Plate Data (48 Measurements)**




Figure 9. Comparison of 3 Flight Maximum Expected Environments (MEE) versus Interface Specification




Figure 10. Comparison of Maximum Enveloping Levels with Statistical Levels

ANALYSIS OF PER NUT FIRING LEVEL

At this point, three families of shock test data exists, LMA 1-9, LMMS 1-2 and LMA 10-12 (Figs. 8,5 and 7). Both the LMA and the LMMS test configurations must be considered equally valid with regards to determining a shock interface level. Also since variation in the separation nut production lot should be accounted for both LMA 1-9 (Lot #1) and LMA 10-12 (Lot #2) need to be considered. Thus, there are three families of equally valid data.

It was decided to calculate a P95/50 level (using lognormal distribution) for each of the three families. A maximum envelope of these three P95/50 curves was then done to define the maximum expected environment (MEE) for a single separation nut firing. This methodology resulted in a peak shock response level of 13, 600 Gs.

ANALYSIS OF PER FLIGHT LEVEL

Since a “successful” flight payload separation system would consists of six separation nuts all firing at or below the MEE level as defined above, it was determined that the per nut MEE level was not sufficient for establishing the spacecraft interface level. For example, if a single nut has a P95/50 probability of success (success defined as being at or below the P95/50 level) then firing six nuts (as in a flight separation) would have only a 74% probability (.95 raised to the 6th power) that none of the six nuts would exceed the P95/50 level.

The binomial distribution can be utilized to find the probability of an event happening exactly X times in N trials given the probability that an event will happen in any single trial. Knowing that the desired interface flight MEE is a P95/50 level, a new calculation can be made for an individual nut level. This calculation would result in an individual nut level which would ensure a P95/50 per flight level (firing of six nuts).

One can calculate that a P99.1/50 per nut firing is equivalent to a P95/50 flight firing of six nuts. That is 0.991 raised to the 6th power is 0.95.

Therefore a P99.1/50 level was calculated for each of the three valid families of test data. Again the maximum envelope of these three curves was made to calculate the new flight MEE level. Due to the fact that the shock test data within a family was so repeatable, the impact of allowing for the successful firing of all six nuts was only approximately 1 dB. The MEE level was raised from 13, 600 Gs (per nut firing) to 15, 200 Gs (per flight), as a result.

After allowing for a one-third octave shift in frequency to account for possible hardware stack up variation, the flight MEE level was closely enveloped to define the final Interface Control Document (ICD) level. This ICD level peaks at 16, 100 Gs. The ICD specification is shown along with the flight MEE for the three families in Fig. 9.

CONCLUSIONS

The sample size is typically small for aerospace shock test data. This often forces the engineer to make assumptions on its population distribution and utilize conservative margins or methodologies in determining specifications. For example, the MEE is often derived by taking the maximum envelope of a limited amount of shock data and adding three to six dB. For the case of the EOS payload separation shock, a large amount of shock test data was available which allowed for some unique statistical analysis and a more accurate definition of the interface shock specification.

A description of the methodology employed on the EOS shock test data and the rationale for using it is provided in this paper. The EOS test series data was analyzed and shown to be lognormally distributed for all four test series. Statistical checks were employed to validate when it was proper to combine test series data. It was found to be valid for only one combination. Finally, the binomial distribution was utilized to go from a per nut MEE level to a per flight MEE level which determined the final interface shock specification for the EOS spacecraft.

This methodology resulted in the flight MEE curves and the ICD specification as shown in Fig. 9. As a check of reasonableness, the maximum envelope of all 78 shock test measurements was determined and plotted against the

maximum envelope of the three flight MEE curves of Fig. 9. This comparison, given in Fig. 10, shows that very similar levels are derived by the maximum enveloping technique and the statistical techniques for this EOS shock test data base. This similarity is due to: (1) the large sample size (78 measurements) of test data, and (2) the relatively small test to test variability (within each test family) of the shock data (as compared to typical shock test data variability). Other shock test databases could yield different results depending on its test to test variability and the number of test measurements.

Further information on the EOS shock separation test programs may be found in the LMA [4] and LMMS [5] contractor test reports.

REFERENCES

1. Manning, J. E., 1991, "Space Station Freedom Work Package 4 Acoustic and Vibration Environment," Cambridge Collaborative Inc. Report 91-12-13109-1.
2. Duncan, A. J. , 1965, *Quality Control and Industrial Statistics*, Richard D. Irwin, Inc., Homewood, Illinois, pp. 916.
3. Himelblau, H., Kern, D. L., Piersol, A. G., 1997, NASA Technical Standard on Pyroshock Test Criteria.
4. Salmon, M , Nickel, D. , 1997, " Intermediate Expendable Launch Vehicle (IELV) Payload Separation System - 77 Inch Test Report - Volume 1", Lockheed Martin Astronautics Space Systems Report IELV-96-020.
5. Mittal, S., Staley, J. , McCue, R., 1996, "EOS AM-1 Spacecraft Structure Shock Test Final Report (VRD-130)", Lockheed Martin Missiles & Space Valley Forge Operations Report EOS-DN-STR-071.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1998		3. REPORT TYPE AND DATES COVERED Technical Memorandum
4. TITLE AND SUBTITLE Statistical Analysis of a Large Sample Size Pyroshock Test Data Set			5. FUNDING NUMBERS WU-257-50-10-00	
6. AUTHOR(S) William O. Hughes and Anne M. McNelis				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135-3191			8. PERFORMING ORGANIZATION REPORT NUMBER E-11057	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/TM-1998-206621	
11. SUPPLEMENTARY NOTES Prepared for the 68th Shock and Vibration Symposium sponsored by the Shock and Vibration Information Analysis Center, Hunt Valley, Maryland, November 3-7, 1997. Responsible person, William O. Hughes, organization code 7735, (216) 433-2597.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Categories: 15, 18, and 65 This publication is available from the NASA Center for AeroSpace Information, (301) 621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The EOS spacecraft will launch on an Atlas IIAS launch vehicle on its mission to planet Earth in late 1998. The new design of the spacecraft's pyroshock separation system was characterized by a series of thirteen separation tests. The analysis methods used to evaluate this unusually large amount of shock data will be discussed in this paper, with particular emphasis on population distributions and finding statistically significant families of data, leading to an overall shock separation interface level.				
14. SUBJECT TERMS Shock; EOS; Statistical analysis; Launch vehicle; Spacecraft testing			15. NUMBER OF PAGES 17	
			16. PRICE CODE A03	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	